



欧司朗LED小甜筒灯泡

LED VALUE STICK

We bring innovation to light!



Product licensee of trademark
OSRAM in general lighting



欧司朗LED小甜筒灯泡

LED VALUE STICK



Item name	Product number (EAN)	[W] ¹	[lm] ¹	[K]	[Ra] ²	[A°] ²	[I [mm]]	[d [mm]]	[t [h]] ³
-----------	-------------------------	------------------	-------------------	-----	-------------------	-------------------	----------	----------	----------------------

E27 灯头

LED Value STICK	4058075128460	7	E27	700	2700	80	NO	200	114	41	15000
LED Value STICK	4058075128507	7	E27	750	6500	80	NO	200	114	41	15000
LED Value STICK	4058075128583	9	E27	900	2700	80	NO	200	114	41	15000
LED Value STICK	4058075128606	9	E27	950	4000	80	NO	200	114	41	15000
LED Value STICK	4058075128620	9	E27	950	6500	80	NO	200	114	41	15000
LED Value STICK	4058075128828	12	E27	1300	2700	80	NO	200	117	45	15000
LED Value STICK	4058075128842	12	E27	1350	4000	80	NO	200	117	45	15000
LED Value STICK	4058075128866	12	E27	1350	6500	80	NO	200	117	45	15000

欧司朗LED小甜筒灯泡

LED VALUE STICK




节能效果一览



LED	incandescent	CFLi
7W	60W	12W
9W	70W	15W
12W	100W	24W

灯罩温度

7W&9W



Tc Max: ≤90°C

12W



Tc Max: ≤90°C

欧司朗LED小甜筒灯泡

LED VALUE STICK



产品优势

- 纤细外观设计，方便在各种灯具中轻松替换
- 极具现代感的设计，与各种不同家装风格相得益彰
- 光线均匀柔和，营造良好氛围
- 即插即用，可靠品质源自德国百年照明品牌。

产品特性

- 发光角度高达200°
- 107lm/w 高光效，环保节能
- 15000 小时的超长寿命，质保24个月
- 适配各种使用E27灯头的白炽灯/节能灯
- 瞬时全亮
- 无汞,无紫外红外

安装指南

- 室内环境使用。
- 在更换灯泡前请切断电源。
- 输入电压: 220-240V
- 频率: 50-60HZ
- 储存温度&湿度范围 (-20°C ~ +80°C, 最大湿度 95%)
- 工作温度&湿度范围 (-20°C ~ +35°C, 最大湿度 95%)
- 用以更换的LED灯泡的重量可能会明显大于被更换的灯泡。灯泡重量的增加可能会降低某些配件和灯座的机械稳定性，并可能影响接触的完整性以及灯泡的固定。

标准符合性声明

- IEC62560(2011+A1: 2015): Self-ballasted LED-lamps for general lighting services by voltage > 50 V – Safety specifications
- IEC 62471/ GB/T20145: Photo biological safety of lamps
- EN 61547 2009: Equipment for general lighting purposes - EMC immunity requirements
- CISPR 15(2013 + A1: 2015): Limits and methods of measurement of radio disturbance characteristics of electrical lighting and similar equipment
- IEC61000-3-2:2014: Limits for harmonic current emissions (equipment input current ≤16 A per phase)
- EN 61000-3-3 Limitation of voltage changes, voltage fluctuations and flicker in public low-voltage supply systems, for equipment with rated current ≤ 16 A per phase and not subject to conditional connection
- IEC 60061 Lamp caps and holders;
- RoHS Directive (EU) 2015/863

废弃处理建议

- Lamps with WEEE sign can be returned at specific collection points.
- LED lamps have to be disposed as special waste.



1. All technical parameters apply to the entire lamp. Because of the complex manufacturing process for light-emitting diodes (LEDs), the specified typical values for LED technical parameters represent only purely statistical variables. They do not necessarily correspond to the actual technical parameters for each individual product which can deviate from the typical value

2. LED lamps can be operated with a wide variety of commercially-available dimmers; details and results of compatibility tests can be seen at www.ledvance.com/dim and in the additional technical product information sheets linked there

3. The average lifetime of LED lamps is defined as the number of hours when the light output of 50% of a large group of identical lamps goes below 70% of its initial luminous flux (L70B50, IEC62612). The lifetime is estimated at room temperature (25 °C), free air burning, base up burning position and at rated voltage

4. The T_c is defined as the highest permissible temperature which may occur on the outer surface of the LED lamp (in the indicated position) under normal operating conditions and at the rated voltage/current/power or the maximum of the rated voltage/current/power range (DIN EN 62031: 2009-01)