

LED T5 晶享支架 3代



产品特征

- 连续发光，无暗区
- 3种色温可选(3000K/4000K/6500K)
- 光束角: 120°
- 2脚插头连接线
- 寿命15,000 h (L70/B50)@25°
- 无汞，绿色环保设计
- 电源线及连接线另配
- 系统光效: 80lm/W
- 功率因数: 0.5
- 输入电压: 220~240V
- 安全认证: CCC & CB

产品应用

- 室内轮廓照明
- 间接线槽
- 层板, 书架
- 灯箱背光

主要规格

长度	功率	光通量	色温	光效	功率因数
300mm	3.4W	270 lm/300lm	3000K 4000K 6500K	80 lm/W	0.5
600mm	6.5W	540 lm/600lm	3000K 4000K 6500K	80 lm/W	0.5
900mm	9.6W	810lm/900 lm	3000K 4000K 6500K	80 lm/W	0.5
1000mm	11W	900lm/1000lm	3000K 4000K 6500K	80 lm/W	0.5
1200mm	13W	1080 lm/1200lm	3000K 4000K 6500K	80 lm/W	0.5

LED T5 晶享支架 3代

产品特征

电器	功率(W)	3.4W	6.5W	9.6W	11W	13W
	输入电压(V)	220 – 240V				
	功率因数	0.5				
	输入电流	28mA	55mA	80mA	95mA	110mA
	频率赫兹	50/60Hz				
	灯具等级	II 类灯具				
光学	光通量	270lm/300lm	540lm/600lm	810lm/900lm	900lm/1000lm	1080lm/1200lm
	系统光效	80	80	80	80	80
	色温(K)	3000K / 4000K / 6500K				
	显色性	≥70				
	芯片	SMD 2835				
	使用寿命	15,000 hrs @ L70 (Ta=25°C)				
	使用环境温度	-20 - +35°C				
灯体	尺寸(长x宽x高mm)	325×22.2×32.5	585×22.2×32.5	885×22.2×32.5	985×22.2×32.5 2.5	1185×22.2×32.5 5
	灯体材料	PC				
	灯体材料	白色				
	防护等级	IP20				

LED T5 晶享支架 3代

订购信息

产品描述	IC	EAN10	EAN40	最小包装数
LDVAL BAT 300 3.4W 3000K G3 24X1 LEDV	AC166700155	4058075273894	4058075273900	24
LDVAL BAT 300 3.4W 4000K G3 24X1 LEDV	AC166710155	4058075273979	4058075273986	24
LDVAL BAT 300 3.4W 6500K G3 24X1 LEDV	AC166720155	4058075273993	4058075274006	24
LDVAL BAT 600 6.5W 3000K G3 24X1 LEDV	AC166730155	4058075274013	4058075274020	24
LDVAL BAT 600 6.5W 4000K G3 24X1 LEDV	AC166740155	4058075274037	4058075274044	24
LDVAL BAT 600 6.5W 6500K G3 24X1 LEDV	AC166750155	4058075274051	4058075274068	24
LDVAL BAT 900 9.6W 3000K G3 24X1 LEDV	AC166760155	4058075274075	4058075274082	24
LDVAL BAT 900 9.6W 4000K G3 24X1 LEDV	AC166770155	4058075274136	4058075274143	24
LDVAL BAT 900 9.6W 6500K G3 24X1 LEDV	AC166810155	4058075274174	4058075274181	24
LDVAL BAT 1200 13W 3000K G3 24X1 LEDV	AC166780155	4058075274303	4058075274310	24
LDVAL BAT 1200 13W 4000K G3 24X1 LEDV	AC166790155	4058075274327	4058075274334	24
LDVAL BAT 1200 13W 6500K G3 24X1 LEDV	AC166800155	4058075274341	4058075274358	24
LDVAL BAT 1000 11W 3000K G3 24X1 LEDV	AC167000155	4058075274365	4058075274372	24
LDVAL BAT 1000 11W 4000K G3 24X1 LEDV	AC167010155	4058075274389	4058075274396	24
LDVAL BAT 1000 11W 6500K G3 24X1 LEDV	AC167020155	4058075274402	4058075274419	24

LED T5 晶享支架 3代


订购信息 - 配件

产品描述	IC	EAN40	最小包装数
LDVAL BAT POWER CABLE G3 VS20 LEDV	AC171140055	4058075282001	20
LDVAL BAT CONNECT CABLE G3 VS20 LEDV	AC171150055	4058075282018	20



电源线: 170mm
 连接线: 265mm

尺寸图



类型	长度
1 尺	325 mm
2 尺	585 mm
3 尺	885 mm
4 尺	1185 mm
1米	985mm

最长串联数

支架 1ft 3.4W – 30 pcs
 支架 2ft 6.5W – 15 pcs
 支架 3ft 9.6W – 10pcs
 支架 4ft 13W – 8 pcs
 支架 1m 11W-8 pcs
 Or <104W 含长度